

10G SFP

Single & Dual Fiber



Product Description

The 10Gbps industrial grade small form-factor pluggable (SFP) transceivers support the connectivity of the fiber optic network. They can support data transmission speed up to 10Gbps. They provide flexibility in the network deployment as they can be hot-pluggable allowing them to be removed or connected without interruption to the network.

The 10Gbps SFP transceivers can operate at a wide operating temperature from -40 degrees Celsius to 85 degrees Celsius, therefore, they are suitable to be deployed in an industrial environment. The SFP transceivers come with the Digital Diagnostic Monitoring (DDM) function which allows functions such as the voltage of supply, temperature, input or output power to be monitored.

Fully compatible with Cisco, HP, Alcatel, H3C, Huawei, Juniper, ZTE, Zyxel, D-Link, Extreme, Nortel, Netgear, Enterasys, Founfry, Adtran, Brocadem Marconi, Finisar etc.

Product Features

- Up to 10Gbps data links
- ➤ WDM DFB/APD laser
- Simplex LC Connector
- Hot-pluggable SFP+ footprint
- Single 3. 3V power supply
- > Operating temperature: 0~70°C/-40~85°C
- > RoHS
- Digital Diagnostic Monitor (DDM)

PRODUCT FEATURES AND SPECIFICATIONS

10G Single & Dual Fiber SFP

Model Number	Data Rate	Distance	Product Description
10G Single Fiber SFP Transceiver			
UB5223-SX-20A/B	10G	20KM	10G Single Fiber SFP - 1270/1310 NM, 20KM
UB5223-SX-40A/B	10G	40KM	10G Single Fiber SFP - 1270/1310 NM, 40KM
UB5223-SX-60A/B	10G	60KM	10G Single Fiber SFP - 1270/1310 NM, 60KM
UB5245-SX-80A/B	10G	80KM	10G Single Fiber SFP - 1490/1550 NM, 80KM
10G Dual Fiber SFP Transceiver			
UB5285-DX	10G	300M	10G Dual Fiber SFP - 850 NM, 300mtr
UB5213-DX-20	10G	20KM	10G Dual Fiber SFP - 1310 NM, 20 KM
UB5215-DX-40E	10G	40KM	10G Dual Fiber SFP - 1550 NM, 40 KM