



E/GPON (XPON) ONU

UB5042 GVW-D

4GE + 2VOICE + DUAL-BAND WIFI

Product Description

UB5042 GVW-D ONU supports EPON/GPON two modes access. The ONU automatically switches into the corresponding PON mode by identifying the local OLT mode to complete GPON/EPON/XPON adaptive access.

UB5042 GVW-D has a high reliability and provides quality of service guarantee, easy management, flexible expansion and networking. It fully meets the ITU-T and IEEE technical standards and has good compatibility with third party OLT.

UB5042 GVW-D integrates wireless function which meets 802.11 a/b/g/n/ac technical standards. At the same time, it also supports 2.4GHz/5GHz dual-band wireless signal. It has the characteristics of strong penetrating power and wide coverage. It can provide users with more efficient data transmission security.

MAIN FEATURES

- In compliant with ITU – T G.984.1/2/3/4 and IEEE802.3ah standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Meet 802.11 a/b/g/n/ac WIFI technical standard
- Support VLAN transparent, tag, untag configuration
- Support multicast function
- Support DHCP/Static/PPPOE internet mode
- Support port-binding
- Support TR069 remote management
- Support data encryption and decryption function
- Support Dynamic Bandwidth Allocation (DBA)
- Support MAC filter and URL access control
- Support H.248 and SIP protocol
- Support power-off alarm function ,easy for link problem detection

PRODUCT FEATURES AND SPECIFICATIONS

UB5042 GVW-D XPON ONU

EPON/GPON Interface

- » SC/UPC single mode single fiber
- » GPON : FSAN G.984.2 standard, Class B+
- » EPON : 1000BASE-PX20+ symmetric
- » GPON : 2.488Gbps/1.244Gbps downstream/upstream
- » EPON : 1.25Gbps downstream/upstream
- » Wavelength: Transmit: 1310nm Receiver: 1490nm
- » Receiving sensitivity: GPON : -28dBm EPON : -27dBm
- » Saturated power: GPON : -8dBm EPON : -3dBm
- » Transmitting power: GPON : 0.5~5dBm EPON:0~4dBm

Network Management

Management Mode

- » OMCI, OAM, TR069, WEB, Telnet

Management Function

- » Status monitor, Configuration management, Alarm management, Log management

Power Interface

- » 12V DC Power supply

Ethernet Interface

- » 4*10/100/1000M auto-negotiation
- » Full/half duplex mode
- » RJ45 connector
- » Auto MDI/MDI-X
- » 100m distance

Physical Features

Power

- » External 12V DC/1A power supply adapter
- » Power consumption: <7W

Physical Specifications

- » Item Dimension : 160mm(L)*139.5mm(W)*28.5mm(H)
- » Item Net Weight : about 239g

Environmental Specifications

- » Operating temperature: 0 to 40°C
- » Operating humidity: 10% to 90 % (Non-condensing)

POTS Interface

- 2*RJ11
- Max 1km distance
- Balanced Ring, 50V RMS

WIFI Specification

- Comply with IEEE 802.11a/b/g/n/ac protocol standard, support 2.4GHz and 5GHz
- There are four external antennas
- 5dBi antenna gain
- Maximum ideal rate up to 1.2Gbps
- 4GHz supports 2*2 MIMO (Multiple-Input Multiple-Output) technology
- 5GHz supports 2*2 MIMO (Multiple-Input Multiple-Output) technology
- Support 8 SSIDs
- Support wider RF bandwidth, up to 80MHz
- Support higher 256-QAM modulation mode
- Support MIMO-OFDM encoding mode
- Support wireless security of 64/128 bit WEP, 1x, WPA and WPA2
- Support mesh function

UBIQCUM INDIA PVT. LTD.

Corporate Office: D-92, First Floor, Sector - 63, Noida, UP-201301 | Website: www.ubiqcom.in | Email: info@ubiqcom.in

Call Us: +91 99 10 77 17 97 | Support Toll Free: 1800-1212-051

Branch Offices: Delhi, Noida, Mumbai, Pune, Chandigarh, Bengaluru, Hyderabad, Ahmedabad, Chennai, Kolkata, Kochi